

## EZI-ACTION DRUM PUMPS



### COLOR-CODED SAFETY STRAPS

6 Colors Available!



### DESCRIPTION:

EZI-action pumps provide an easy method of dispensing a wide range of liquids including strong acids, alkalis, mild solvents, lubricants, oils, and diesel to name a few from 5 gallon (19 Litres) containers to 55 gallon (208 Litres) drums. The pumps dispense fluid on both the up and down stroke with only two moving parts. Patented zero-friction design provides effortless flow of viscous fluids up to 8,800 cps (8000 cSt). The pumps are ruggedly constructed with polypropylene and polyethylene to perform in hostile conditions. Each EZI-action pump is supplied with the appropriate adapters for quick and easy installation.

All EZI-action pumps feature a safety strap, which locks the pump handle in the closed position to prevent accidental discharge of liquids when not in use. Optional color-coding of the Safety Strap, when used in conjunction with fluid transferring and dispensing containers, such as Oil Safe containers, minimize the risk of fluid cross-contamination and ensures the right lubricant is used in your equipment.

**FEATURES:**

- Easy to install, safe to use, and simple to maintain
- Fits 5 (19L) to 55 gallon (208L) containers
- Pumps liquid on both the “up” and “down” strokes
- Sits on the base of the container
- Prevents undesired fluid drip
- Pumps high viscosity liquids
- Optional colour-coding system available
- No wearing parts
- Not to be used with highly flammable liquids, strong solvents, or gasoline

**SPECIFICATIONS:**

Material	Polypropylene and Polyethylene
Maximum Viscosity	8,000 cps (8000 cSt)
Maximum Flow	5-6 Gallon Drum Pump – 6 oz per stroke (19 – 22 Litre Drum pump - 177 cc per stroke) 15-30 Gallon Drum Pump – 15 oz per stroke (56 – 113 Litre Drum Pump – 443 cc per stroke) 15-55 Gallon Drum Pump – 15 oz per stroke (56 – 208 Litre Drum Pump – 443cc per stroke)