

STREAMLINER DC



Delivery time is easily set with a simple twist of an allen key on top of the unit. The dispensing time of the Streamliner DC is variable between one and twelve months allowing complete control over the amount of lubricant being applied.

The transparent housing provides visual confirmation of the rate of delivery. Unlike opaque lubricators, one quick glance is all that is needed to see just how much lubricant is left in the cartridge.

The light weight, compact design of the Streamliner DC allows for installation in almost any place and any position, even under water.

FEATURES:

- Simple to install and activate
- Powered by a patented gas generating dry cell
- Adjustable time setting from 1 to 12 months reduces inventory costs, less units to have available
- Transparent chamber allows easy visual check of lubricant level
- Sealed point of contact prevents contamination with dirt and water - submersible in any direction
- Easy adjustment of dispensing rate during operation
- Environmentally friendly
- Can be temporarily deactivated
- Custom filling with grease or oil is available
- Intrinsically safe - Class I, II, III; Division 1; Groups A, B, C, D, E, F, and G

(Streamliner DC cont)

SPECIFICATIONS:

Grease Capacity	30, 60, or 125 cc
Power Generation	Hydrogen Gas Producing Dry Cells
Working Pressure	Max. 72 PSI (5 bar)
Dispensing Quantity	0.08 - 8.3 cc/day
Operating Temperature	-4°F to 131°F (-20°C to 55°C)
Seven Standard Greases	Mobilgrease XHP 222 Exxon Unirex EP 2 Mobilith SHC 100 Mobilgrease FM 222 Mobilith SHC 220 Mobilith SHC PM 460 Mobil Polyrex EM
Non Standard Greases	These units can be filled with the customer's own grease or oil.
Thread Size	1/4" NPT