

STREAMLINER V



DESCRIPTION:

Streamliner™ V grease dispensers are designed for applications where it is essential to have precise amounts of grease delivered to critical machine parts and are a cost-effective alternative to fully integrated lube systems or manual lubrication. The Streamliner V grease dispensers have a variable dispensing rate from 1 to 12 months and is controlled by a microprocessor to ensure reliable and predictable lubricant delivery.

FEATURES:

- Comes pre-filled with one of six standard grease types
- Electro-chemical drive with microprocessor control
- Large LCD display
- Six variable dispensing rates - 1, 2, 3, 6, 12 months, and purge
- Auto purge cut-out
- Economical 250cc grease capacity
- Green LED indicates unit operation
- Transparent reservoir for easy viewing of grease level
- Inert gas generation

(Streamliner V cont.)

SPECIFICATIONS:

Operating Temperature	-4°F to 140°F (-20°C to 60°C)
Maximum Working Pressure	80psi (551 kPa)
Dispensing Rates	1, 2, 3, 6, 12 months, and purge
Six Standard Greases	Mobilgrease XHP 222 Exxon Unirex EP2 Mobil SHC 100 Mobilgrease FM 222 Mobilith SHC 220 Mobilith SHC PM 460
Anti-Explosive Certi Grade	Ex ia I/II B T6